



Ref. No. NB(Bihar) /DPSP/ Tender-Parking Shed/ 102 /2023-24

20 April 2023

To  
All Category-III Empanelled Vendor for Civil Work  
Patna -

Dear Sir,

**Renovation of Parking Shed of NABARD Office, Maurya Lok Complex, Patna**

It has been decided to undertake renovation of the NABARD parking shed at Maurya Lok Complex, Dak Bunglow Road, Patna-800001.

Accordingly, you are advised to submit the price bid for BOQ enclosed herewith for renovation of the parking shed. The Price BID may be submitted in sealed envelope latest by on/ before 11 May 2023 (17:00 Hrs.)

सधन्यवाद/ Regards

B.N. Singh  
Assistant General Manager



राष्ट्रीय कृषि और ग्रामीण विकास बैंक  
National Bank for Agriculture and Rural Development

बिहार क्षेत्रीय कार्यालय, मौर्य लोक कॉम्प्लेक्स, ब्लॉक "बी" चौथी एवं पाँचवीं मंजिल, डाक बंगला रोड, पटना-800 001  
ई-मेल : patna@nabard.org, फोन नं: 0612-2223985, फैक्स नं: 2238424

Bihar Regional Office, Maurya lok Complex, Block "B", 4th & 5th Floor, Dak Bunglow Road, Patna-800 001, E-mail : patna@nabard.org, Tel. : 0612-2223985, Fax : 2238424

## BOQ for NABARD Parking Shed at Maurya lok Complex, Patna-1

SL No.	As per BOQ	DESCRIPTION	UNIT	QTY
1	2	3	4	5
1	10.32	Steel work welded in built up sections/framed work including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required.		
	10.32.2	In gratings, frames, guard bar, ladders,		
			<b>KG</b>	<b>47.88</b>
2	12.1	Providing corrugated G.S. sheet roofing fixed with G.I.J. or hooks, bolts and nuts 8 mm diameter with bitumen and G. I. limpet washers or with G.I. limpet washers filled with white lead and including a coat of approved steel primer and two coats of approved paint on over lapping of sheets complete (upto a pitch of 60°) excluding the cost or purlins, rafters and trusses.		
	12.1.3	1.00 mm thick with zinc coating not less than 275 gm/mz		
			<b>SQM</b>	<b>286.17</b>
3	11.20	Chequerred precast cement concrete tiles 22 mm thick with marbie chips of size 6 mm in footpath & coutyard jointed with neat cement slurry mixed with pigment to match the shade of tiles including rubbing and cleaning tec. Complete on 20 mm thick bed of cement mortar 1:4(1 cement:4 coarse sand)		
	11.20.1	Light shade using white cement		
		Chequerred Tiles Flooring		
			<b>SQM</b>	<b>163.02</b>

SL No.	As per BOQ	DESCRIPTION	UNIT	QTY
4	10.36	Providing and fixing stainless steel railing ( Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners , stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in-charge, ( for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).		
		Main Entrance Gate		
			<b>KG</b>	<b>168.75</b>
5	21.17	Providing and fixing anodised aluminium grill (anodised transparent or dyed to required shade according to IS: 1868 with minimum anodic coating of grade AC 15) of approved design/pattern, with approved standard section and fixed to the existing window frame with C.P. brass/ stainless steel screws @ 200 mm centre to centre, including cutting the grill to proper opening size for fixing and operation of handles and fixing approved anodised aluminium standard section around the opening, all complete as per requirement and direction of Engineer-in-charge. (Only weight of grill to be easured		
			<b>sqm</b>	<b>67.91</b>
			<b>KG</b>	<b>305.57</b>

SL No.	As per BOQ	DESCRIPTION	UNIT	QTY
6	21.1.1.2	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : Powder coated aluminium (minimum thickness of powder		
			<b>KG</b>	<b>135.81</b>
7	13.94	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:		
	13.94.1	Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.		
			sqm	<b>67.13</b>
8	D-1.55.3	Wiring for group controlled (looped) light point/fan point/exhaust fan point/ call bell point (without independent switch etc.) with 1.5 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed steel conduit, and earthing the point with 1.5 sq. mm FRLS PVC insulated copper conductor single core cable etc. as required. Group C		
			point	10.00
9	CIVIL 10.17	Providing and fixing M.S. Fan clamp type I or II of 16 mm dia M.S. bar, bent to shape with hooked ends in R.C.C. slabs or beams during laying, including painting the exposed portion of loop, all as per standard design complete as required.		
		For Fan	no.	1.00

SL No.	As per BOQ	DESCRIPTION	UNIT	QTY
10	8.11.3	Supply and installation of regular/standard model A.C. ceiling fan of 1400 mm sweep including wiring the down rods of standard length (upto 30 cm) with 1.5 sq. mm FR PVC insulated copper conductor etc as required.		
		Fan	no.	1
		2 x 4 sq.mm. + 1 x 4 sq.mm. earth wire	Metre	50.00
11	BSR 5.9.3	Supplying and fixing single wall mounted 18/22 watt LED type batten fitting complete with electronic driver and LED tube etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated copper conductor and earthing the body etc. as required.		
		Led tube	nos	6
12	15.7	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead:		
	15.7.3	in lime mortar		
		Total	cum	3.93
13	15.28	Dismantling roofing including ridges, hips valleys and gutters etc. and stacking the material within 50 metres lead of:		
	15.28.2	Asbestos sheet		
		Roof Area		
			SQM	204.45
	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.		
			cum	19.26
14	15.17	Dismantling steel work in single sections including dismembering and stacking within 50 meters lead in:		
		15.17.2 Channels,angles, tees and flats		
			KG	765.82
15	MR	Signage/Signboard	LS	
		<b>Amount</b>		
		<b>GST</b>		
		<b>Total Amount</b>		
		<b>Total Amount in Words:</b>		